

**CITY OF KANSAS CITY, MISSOURI**

**SUPPLEMENT TO**

**APWA STANDARD SPECIFICATIONS AND DESIGN CRITERIA**

**SECTION 2400**

This is Kansas City, Missouri supplement to Section 2400, APWA Standard Specification and Design Criteria. The following additions, deletions and/or revisions are adopted for use and shall become a part of Section 2400 for use within Kansas City, Missouri.

2403 MEASUREMENTS AND PAYMENTS

2403.4.B.2. Paragraph 2403.4.B.2. shall be deleted and the following 2403.4.B.2. shall be added in lieu thereof:

2403.4.B.2. Sanitary Sewer Construction: Sodding will be measured horizontally in linear feet (decimetre) along the centerline of sewer, regardless of width of disturbed areas or type of sod used. Sodding will be measured only when centerline of sewer lies in grassed areas to be sodded as shown on the plans. When the centerline of sewer lies in areas that are not grassed, such as street paving, driveways, parking areas, gardens, etc., no measurement will be made. Areas that are disturbed which lie outside the Contractor's normal trenching operation areas will not be measured for payment, but shall be restored to a condition equal to or better than that existing prior to construction. Each area measured will be measured as either seeding or sodding, but not as both. When sewer ends in grassed areas, measurement will be made only to centerline of manhole.

This Supplement shall become effective January 1, 1990. It supersedes all previous supplements to this section.

890738

George L. Satterlee, P. E.  
Director of Public Works  
of Kansas City, Missouri